



PANEL HEATERS



WARM YOU UP ELEGANTLY

Panel heaters enable fast heating wherever needed. The air from the room enters the heater through the opening on the bottom. Electric heater warms the air with a help of aluminium exchanger. Warm air slowly rises and circles in the room, and therefore quickly and efficiently heats up the room. The outlet of the hot air is directed to the room and not to the wall, which also prevents the wall from getting dark. Thanks to its modern, elegant and slim design it is perfect addition to your home.



FREESTANDING OR WALL-MOUNTED

All models offer a freestanding or wall-mounted solution. Move the appliance to the place where heating is needed, or position it on fixed location with attached hanger.



ECO FUNCTION

The heater contains two heating elements (2x1000W), which you can individually switch on, according to the room temperature you would like to have.



SILENT OPERATION

The heater's operation is almost completely silent and it will not disturb you at all. Just relax and enjoy.



PANEL HEATER OPTIHEAT 2000MP



WALL-MOUNTED OPTION

Easy to install

Wall mounting is perfect for fixed positioning. Thanks to the included hanger, the installation of the heater is extremely easy. Because of the slim design, the use of the space is optimal.






The heater allows setting the heating temperature between 16 and 40 °C. With the simple controls, you can make sure the temperature in the room is always perfect for you.



The heater has built-in overheating protection. Thus, the inside of the heater is protected from overheating that could, in turn, cause overheating of electronic parts and the heating elements.



PANEL HEATER OPTIHEAT 2000EWP



WI-FI CONTROL

Connecting the heater to your home WI-FI network

Connect your heater to your home WI-FI network and easily operate it with the Tuya Smart app that you can download to your smart device. You can monitor and change the heater settings when you are at work, on the road or even on vacation.





The heater allows setting the heating temperature between 15 and 35 °C. With the simple controls, you can make sure the temperature in the room is always perfect for you.



The heater has built-in overheating protection. Thus, the inside of the heater is protected from overheating that could, in turn, cause overheating of electronic parts and the heating elements.



Wall mounting is perfect for fixed positioning. Thanks to the included hanger, the installation of the heater is extremely easy. Because of the slim design, the use of the space is optimal.



PANEL HEATER OPTIHEAT 2000GTP



TOUCH CONTROL

Easy to use

Modern sensor technology allows clear and simple touch-control operation. Enjoy full heating control at your fingertips.





The heater allows setting the heating temperature between 16 and 40 °C. With the simple controls, you can make sure the temperature in the room is always perfect for you.



The heater has built-in overheating protection. Thus, the inside of the heater is protected from overheating that could, in turn, cause overheating of electronic parts and the heating elements.



Wall mounting is perfect for fixed positioning. Thanks to the included hanger, the installation of the heater is extremely easy. Because of the slim design, the use of the space is optimal.



PANEL HEATER OPTIHEAT 2000GTWP



TEMPERED GLASS

Optimal resistance

Tempered glass is more heat resistant than normal glass. It has a high bending strength and is more heat resistant. One of the main features is that if it breaks, it will crumble into small granular chunks instead of splintering into jagged shards as normal glass does.





The heater allows setting the heating temperature between 16 and 40 °C. With the simple controls, you can make sure the temperature in the room is always perfect for you.



The heater has built-in overheating protection. Thus, the inside of the heater is protected from overheating that could, in turn, cause overheating of electronic parts and the heating elements.



Wall mounting is perfect for fixed positioning. Thanks to the included hanger, the installation of the heater is extremely easy. Because of the slim design, the use of the space is optimal.



TECHNICAL CHARACTERISTICS:









MODEL NAME	OPTIHEAT 2000MP	OPTIHEAT 2000EWP	OPTIHEAT 2000GTP	OPTIHEAT 2000GTWP
Product code	731710	731709	731711	731901
Power (W)	2000	2000	2000	2000
Tempered glass panel	NO	NO	YES	YES
Controls	Mechanical	Touch control	Touch control	Touch control
Adjustable thermostat control	NO	YES	YES	YES
LED display	NO	YES	YES	YES
WI-FI control	NO	YES	NO	NO
Timer	NO	Up to 24 hours	Up to 24 hours	Up to 24 hours
Remote control	NO	NO	YES	YES
Temperature range	16 - 40 °C	15 - 35 °C	16 - 40 °C	16 - 40 °C
Free standing option	YES	YES	YES	YES
Wall mounted option	YES	YES	YES	YES
Child lock	NO	YES	YES	YES
Overheat protection	YES	YES	YES	YES
Coverage area	Up to 20 m²	Up to 20 m ²	Up to 20 m ²	Up to 20 m ²
Colour	White	White	Black	White
Sound control signal	NO	YES	YES	YES

WEIGHT AND DIMENSIONS

Dimensions - WxLxH (mm)	920 x 240 x 430			
Net weight (kg)	5.5	5.6	7.4	7.4

www.gorenje.com